



KOP-FLEX™



Image differs from product

Weight:	259.60 LB
UOM:	EA
List Price:	\$66,802.54

WHERE TO BUY

KEY FEATURES

- Close Coupled disc coupling design with reversible hubs to accommodate various shaft separations.
- Unitized Disc Packs for ease of maintenance.
- HT (High Torque) disc packs for medium duty applications.
- Meet AGMA Class 9 balance off the shelf, may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

General Specifications

Technical Specifications

Axial Capacity (+/-):	0.25	Bore Size Min (in):	5.5 in
Bore Type:	Finished Bore	Configuration:	2 standard hubs
Coupling Size:	454	Hub Material:	Carbon Steel
Length Through Bore standard hub (in):	5.12 in	Outside Diameter (in):	15.56 in
Style:	KD11	Torque [Max] (ft-lb):	42,500 ft/lbs
Torque Rating (in-lb):	255,000 in/lbs	Total Length (One Hub Reverse) (in):	12.44 in
Total Length (Std Hub Post) (in):	10.56 in	Total Length (Two Hub Reverse) (in):	14.31 in
Total WR2 (lb-in2):	5,220 psi		

Print

- [2D/3D CAD](#)
- [Catalog Page](#)
- [Installation Manual](#)

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS