



Part #: 2287217 Catalog #: 153 KD 2 SS438



List Price: \$7,759.35

WHERE TO BUY

☐ **Compare Product**

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- MT (Medium Torque) disc packs for medium duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

Axial Capacity (+/-):	0.075	Bore Size Min (in):	0.75 in
Bore Type:	Rough Bore	Configuration:	2 standard hubs
Coupling Size:	153	Disc Coupling Type:	Spacer Coupling
Disc Shape:	Scalloped	Hub Diameter (in):	4.12 in
Hub Material:	Carbon Steel	Length Through Bore standard hub (in):	2 in
Outside Diameter (in):	5.69 in	Stock C Dimension:	4.375
Style:	KD2	Torque [Max] (ft-lb):	1,313 ft/lbs
Torque Rating (in-lb):	7,880 in/lbs	Total Length (Std Hub Post) (in):	8.375 in
Total WR2 (lb-in2):	93.1 psi		

 How can we improve our Product Information?

Print

Resource Center

 2D/3D CAD

[↗ Catalog Page](#)

 [Installation Manual](#)

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS