



POPULAR

Kop-Flex Disc Coupling - Style KD2 - Size 153 - Rough Bore - 153 KD 2 SS700

Part #: 2287233 Catalog #: 153 KD 2 SS700



☐ Add to Compare



Image differs from product

Weight: 32.04 LB

UOM: EA

List Price: \$7,759.35

WHERE TO BUY

☐ Compare Product

How can we improve our Product Information?

Print

Resource Center

2D/3D CAD

Catalog Page

Installation Manual

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- MT (Medium Torque) disc packs for medium duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

Technical Specifications	General Specifications
Technical Specifications	
Axial Capacity (+/-):	0.075
Bore Type:	Rough Bore
Coupling Size:	153
Disc Shape:	Scalloped
Hub Material:	Carbon Steel
Length Through Bore standard hub (in):	2 in
Stock C Dimension:	7
Torque [Max] (ft-lb):	1,313 ft/lbs
Total Length (Std Hub Post) (in):	11 in

Bore Size Min (in):	0.75 in
Configuration:	2 standard hubs
Disc Coupling Type:	Spacer Coupling
Hub Diameter (in):	4.12 in
Length Through Bore (in):	2 in
Outside Diameter (in):	5.69 in
Style:	KD2
Torque Rating (in-lb):	7,880 in/lbs
Total WR2 (lb-in2):	93.1 psi