



POPULAR

# Kop-Flex Disc Coupling - Style KD2 - Size 303 - Rough Bore - 303 KD 2 SS700

Part #: 2287282    Catalog #: 303 KD 2 SS700



☐ Add to Compare



Image differs from product

Weight: 123.45 LB

UOM: EA

List Price: \$31,065.14

WHERE TO BUY

☐ Compare Product

How can we improve our Product Information?

Print

Resource Center

2D/3D CAD

Catalog Page

Installation Manual

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- MT (Medium Torque) disc packs for medium duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

| Technical Specifications               | General Specifications |
|----------------------------------------|------------------------|
| Technical Specifications               |                        |
| Axial Capacity (+/-):                  | 0.125                  |
| Bore Type:                             | Rough Bore             |
| Coupling Size:                         | 303                    |
| Disc Shape:                            | Scalloped              |
| Hub Material:                          | Carbon Steel           |
| Length Through Bore standard hub (in): | 3.38 in                |
| Stock C Dimension:                     | 7                      |
| Torque [Max] (ft-lb):                  | 6,300 ft/lbs           |
| Total Length (Std Hub Post) (in):      | 13.76 in               |

|                           |                 |
|---------------------------|-----------------|
| Bore Size Min (in):       | 1.5 in          |
| Configuration:            | 2 standard hubs |
| Disc Coupling Type:       | Spacer Coupling |
| Hub Diameter (in):        | 6.75 in         |
| Length Through Bore (in): | 3.38 in         |
| Outside Diameter (in):    | 9.25 in         |
| Style:                    | KD2             |
| Torque Rating (in-lb):    | 37,800 in/lbs   |
| Total WR2 (lb-in2):       | 989 psi         |