



Part #: 2430684 Catalog #: 204 KD 20 SS900



Weight: 53.51 LB

UOM: EA

List Price: \$12,535.92

WHERE TO BUY

☐ **Compare Product**

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- HT (High Torque) disc packs for medium and heavy duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

Axial Capacity (+/-):	0.11	Bore Size Min (in):	1 in
Bore Type:	Rough Bore	Configuration:	2 standard hubs
Coupling Size:	204	Disc Coupling Type:	Spacer Coupling
Disc Shape:	Scalloped	Hub Diameter (in):	4.75 in
Hub Material:	Carbon Steel	Length Through Bore standard hub (in):	2.25 in
Outside Diameter (in):	6.62 in	Stock C Dimension:	9
Style:	KD20	Torque [Max] (ft-lb):	6,000 ft/lbs
Torque Rating (in-lb):	36,000 in/lbs	Total Length (Std Hub Post) (in):	13.5 in
Total WR2 (lb-in2):	230 psi		

 How can we improve our Product Information?

Print

Resource Center

[↗ 2D/3D CAD](#)

 [Catalog Page](#)

 [Installation Manual](#)

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS