



Part #: 2430726 Catalog #: 254 KD 20 SS700



WHERE TO BUY

☐ **Compare Product**

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- HT (High Torque) disc packs for medium and heavy duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

Axial Capacity (+/-):	0.14	Bore Size Min (in):	1 in
Bore Type:	Rough Bore	Configuration:	2 standard hubs
Coupling Size:	254	Disc Coupling Type:	Spacer Coupling
Disc Shape:	Scalloped	Hub Diameter (in):	5.75 in
Hub Material:	Carbon Steel	Length Through Bore standard hub (in):	2.88 in
Outside Diameter (in):	7.88 in	Stock C Dimension:	7
Style:	KD20	Torque [Max] (ft-lb):	8,667 ft/lbs
Torque Rating (in-lb):	52,000 in/lbs	Total Length (Std Hub Post) (in):	12.76 in
Total WR2 (lb-in2):	510 psi		

CONTACT OUR EXPERTS

Print