



Kop-Flex Disc Coupling - Style KD20 - Size 304 - Finished Bore - 304 KD 20 SS900 FB

Part #: 2431088 Catalog #: 304 KD 20 SS900 FB

KOP-FLEX™

☐ Add to Compare



Weight: 138.12 LB

UOM: EA

List Price: \$34,562.41

WHERE TO BUY

☐ Compare Product

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- HT (High Torque) disc packs for medium and heavy duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

Axial Capacity (+/-): **0.17**
Bore Type: **Finished Bore**
Coupling Size: **304**
Length Through Bore standard hub (in): **3.38 in**
Stack C Dimension: **9**
Torque [Max] (ft-lb): **14,833 ft/lbs**
Total Length (Std Hub Post) (in): **15.76 in**

Bore Size Min (in): **1.5 in**
Configuration: **2 standard hubs**
Hub Material: **Carbon Steel**
Outside Diameter (in): **9.25 in**
Style: **KD20**
Torque Rating (in-lb): **89,000 in/lbs**
Total WR2 (lb-in2): **1,190 psi**

How can we improve our Product Information?

Print

Resource Center

- [2D/3D CAD](#)
- [Catalog Page](#)
- [Installation Manual](#)

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS