



Part #: 2431351 Catalog #: 304 KD 20 LS800

☐ **Add to Compare**

List Price: \$30,390.71



WHERE TO BUY

☐ **Compare Product**

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- HT (High Torque) disc packs for medium and heavy duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

Axial Capacity (+/-):	0.17	Bore Size Min (in):	1.5 in
Bore Type:	Rough Bore	Configuration:	1 long hub/1 standard hub
Coupling Size:	304	Disc Coupling Type:	Spacer Coupling
Disc Shape:	Scalloped	Hub Diameter (in):	6.75 in
Hub Material:	Carbon Steel	Length Through Bore (in):	3.38 in
Length Through Bore (long hub) (in):	4.75 in	Length Through Bore standard hub (in):	3.38 in
Outside Diameter (in):	9.25 in	Stock C Dimension:	8
Style:	KD20	Torque [Max] (ft-lb):	14,833 ft/lbs
Torque Rating (in-lb):	89,000 in/lbs	Total Length (Std Hub Post) (in):	16.13 in
Total WR2 (lb-in2):	1,190 psi		

 [Installation Manual](#)

Print

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS