



POPULAR

Kop-Flex Disc Coupling - Style KD20 - Size 304 - Rough Bore - 304 KD 20 SS700

Part #: 2430783 Catalog #: 304 KD 20 SS700



☐ Add to Compare

Image differs from product

Weight:

135.68 LB

UOM:

EA

List Price:

\$30,077.84

WHERE TO BUY

☐ Compare Product

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- HT (High Torque) disc packs for medium and heavy duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

How can we improve our Product Information?

Print

Resource Center

2D/3D CAD

Catalog Page

Installation Manual

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS

PRODUCT SPECIFICATIONS			
Technical Specifications		General Specifications	
Technical Specifications			
Axial Capacity (+/-):	0.17	Bore Size Min (in):	1.5 in
Bore Type:	Rough Bore	Configuration:	2 standard hubs
Coupling Size:	304	Disc Coupling Type:	Spacer Coupling
Disc Shape:	Scalloped	Hub Diameter (in):	6.75 in
Hub Material:	Carbon Steel	Length Through Bore (in):	3.38 in
Length Through Bore standard hub (in):	3.38 in	Outside Diameter (in):	9.25 in
Stock C Dimension:	7	Style:	KD20
Torque [Max] (ft-lb):	14,833 ft/lbs	Torque Rating (in-lb):	89,000 in/lbs
Total Length (Std Hub Post) (in):	13.76 in	Total WR2 (lb-in2):	1,190 psi

https://www.regalrexnord.com/products/couplings/disc-couplings/disc-coupling-style-kd20-size-304-rough-bore-2430783

1/1