



Part #: 2430858 Catalog #: 354 KD 20 SS1000

☐ **Add to Compare**

List Price: \$64,577.66

WHERE TO BUY

☐ **Compare Product**

KEY FEATURES

- Spacer coupling with factory-assembled center section for easy assembly.
- Specifically engineered to meet API 610 specifications.
- HT (High Torque) disc packs for medium and heavy duty applications.
- Meet AGMA Class 9 balance off the shelf, and may be balanced to AGMA Class 10 or 11.

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

Axial Capacity (+/-):	0.2	Bore Size Min (in):	2 in
Bore Type:	Rough Bore	Configuration:	2 standard hubs
Coupling Size:	354	Disc Coupling Type:	Spacer Coupling
Disc Shape:	Scalloped	Hub Diameter (in):	7.75 in
Hub Material:	Carbon Steel	Length Through Bore (in):	4 in
Length Through Bore standard hub (in):	4 in	Outside Diameter (in):	10.75 in
Stock C Dimension:	10	Style:	KD20
Torque [Max] (ft-lb):	25,000 ft/lbs	Torque Rating (in-lb):	150,000 in/lbs
Total Length (Std Hub Post) (in):	18 in	Total WR2 (lb-in2):	2,630 psi

 How can we improve our Product Information?

Resource Center

 2D/3D CAD

 [Catalog Page](#)

 [Installation Manual](#)

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS

Print