



Rexnord Thomas 10402565 CMR Disc Coupling - 10402565

Part #: 10402565 Catalog #: 10402565



☐ Add to Compare



Weight: 1.23 LB
UOM: EA

WHERE TO BUY

☐ Compare Product

KEY FEATURES

- Size 925 CMR Disc Coupling for packaging a Waukesha 16V275GL engine to Ariel JGC/6 compressor

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

Available Shaft Length (in):	9 in
Bolt Circle Diameter (in):	27.25 in
Bolting:	SAE
Bore Diameter [Min] (in):	7.4927 in
Connection Type:	STR BORE, NO KEYWEY
Coupling Size:	925
Driven Mount Style:	Keyless Hub
Engine:	Waukesha 16V275GL
Flywheel Adapter Diameter (in):	28.875 in
Horsepower:	4,835 Hp
Number of Cylinders (Engine):	16
Overall Length (in):	26.24 in
Product:	CMR

Available Shaft Sizes (in):	7.5000/7.4990 in
Bolt Hole Diameter (in):	0.78 in
Bore Diameter [Max] (in):	7.4942 in
Compressor:	Ariel JGC/6
Continuous Torque Rating (in-lb):	1,281,280 in/lbs
Disc Pack Material:	TD – Tomaloy (Standard)
Driver Mount Style:	Flywheel Adapter
Flywheel Adapter Bolt Quantity:	12
Flywheel Adapter Material:	Carbon Steel
Number of Cylinders (Compressor):	6
Operating Speed (rpm):	1,000 rpm
Peak Overload Torque (in/lbs):	1,537,536 in/lbs
Series:	Thomas AMR & CMR Couplings

How can we improve our Product Information?

Print

Resource Center

INSTALLATION MANUAL

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS