



Jaure Barflex Barflex Coupling -Style TCBR - Heavy Duty Standard Design - Size 130 -Full Flex -Rough Bore - BARFLEX TCBR-0130 A00

Part #: ABBR0010006 Catalog #: BARFLEX TCBR-0130 A00



☐ Add to Compare

Weight: 79.37 LB

UOM: EA

WHERE TO BUY



☐ Compare Product

KEY FEATURES

- About 10% higher torque capacity, allowing a more favorable size selection and thus an important cost saving
- Assembly time reduction
- Increased axial misalignment tolerance
- Improved visual wear indicator. Easier to read wear

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

Bolt Circle:	320
Bore Size Max (in):	4.53 in
Bore Type:	Rough Bore
Compatible Bore Size [Min] (mm):	78 mm
Coupling Size:	130
Fastener Quantity:	10
Hub Diameter (mm):	174 mm
Length Through Bore (in):	5.12 in
Lube/Non-Lube:	Lubricated
Maximum Displacement (+/-) (mm):	4 mm
Outside Diameter (in):	14.17 in
Overall Length (in):	5.28 in
Radial Load (N):	41,800 N
Style:	TCBR
Torque [Max] (in-lb):	207,992.53 in/lbs

Bolt Type:	Exposed Bolt
Bore Size Max (mm):	115 mm
Compatible Bore Size [Min] (in):	3.07 in
Configuration:	Full Flex Coupling
Coupling Type:	Barflex Coupling
Flange Thickness (mm):	15 mm
Includes:	Hub (1) Sleeve (1) Cover (1) Pin (1) Pointer (1) Seeger Ring (1) Barrel Set (1) Fastner Set (1)
Length Through Bore (mm):	130 mm
Material:	Alloy Steel
Maximum Operating Angular Misalignment:	1 °
Outside Diameter (mm):	360 mm
Overall Length (mm):	134 mm
Sleeve Type:	Flanged
Temperature Range:	-15°C to 60°C
Torque [Max] (N-m):	23,500 N-m

How can we improve our Product Information?

Resource Center

2D/3D CAD

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS

Print