



Jaure Barflex Barflex Coupling -Style TCBR - Heavy Duty Standard Design - Size 400 -Full Flex -Rough Bore - BARFLEX TCBR-0400 A00

Part #: ABBR0010011    Catalog #: BARFLEX TCBR-0400 A00



☐ Add to Compare

Weight: 231.49 LB

UOM: EA

WHERE TO BUY



☐ Compare Product

KEY FEATURES

- About 10% higher torque capacity, allowing a more favorable size selection and thus an important cost saving
- Assembly time reduction
- Increased axial misalignment tolerance
- Improved visual wear indicator. Easier to read wear

PRODUCT SPECIFICATIONS

Technical Specifications

General Specifications

Technical Specifications

|                                  |                   |
|----------------------------------|-------------------|
| Bolt Circle:                     | 400               |
| Bore Size Max (in):              | 7.28 in           |
| Bore Type:                       | Rough Bore        |
| Compatible Bore Size [Min] (mm): | 98 mm             |
| Coupling Size:                   | 400               |
| Fastener Quantity:               | 10                |
| Hub Diameter (mm):               | 273 mm            |
| Length Through Bore (in):        | 7.28 in           |
| Lube/Non-Lube:                   | Lubricated        |
| Maximum Displacement (+/-) (mm): | 4 mm              |
| Outside Diameter (in):           | 17.72 in          |
| Overall Length (in):             | 7.44 in           |
| Radial Load (N):                 | 82,500 N          |
| Style:                           | TCBR              |
| Torque [Max] (in-lb):            | 506,262.66 in/lbs |

|                                         |                                                                                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------|
| Bolt Type:                              | Exposed Bolt                                                                                    |
| Bore Size Max (mm):                     | 185 mm                                                                                          |
| Compatible Bore Size [Min] (in):        | 3.86 in                                                                                         |
| Configuration:                          | Full Flex Coupling                                                                              |
| Coupling Type:                          | Barflex Coupling                                                                                |
| Flange Thickness (mm):                  | 20 mm                                                                                           |
| Includes:                               | Hub (1) Sleeve (1) Cover (1) Pin (1) Pointer (1) Seeger Ring (1) Barrel Set (1) Fastner Set (1) |
| Length Through Bore (mm):               | 185 mm                                                                                          |
| Material:                               | Alloy Steel                                                                                     |
| Maximum Operating Angular Misalignment: | 1 °                                                                                             |
| Outside Diameter (mm):                  | 450 mm                                                                                          |
| Overall Length (mm):                    | 189 mm                                                                                          |
| Sleeve Type:                            | Flanged                                                                                         |
| Temperature Range:                      | -15°C to 60°C                                                                                   |
| Torque [Max] (N-m):                     | 57,200 N-m                                                                                      |

How can we improve our Product Information?

Print

Resource Center

2D/3D CAD

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS