



Jaure Barflex Barflex Coupling -Style TCBR - Heavy Duty Standard Design - Size 600 -Full Flex -Finish Bore - BARFLEX TCBR-0600 B01

Part #: ABBR0010038 Catalog #: BARFLEX TCBR-0600 B01



☐ Add to Compare

UOM: EA

WHERE TO BUY



☐ Compare Product

KEY FEATURES

- About 10% higher torque capacity, allowing a more favorable size selection and thus an important cost saving
- Assembly time reduction
- Increased axial misalignment tolerance
- Improved visual wear indicator. Easier to read wear

PRODUCT SPECIFICATIONS

Technical Specifications

Technical Specifications			
Bolt Circle:	500	Bolt Type:	Exposed Bolt
Bore Size Max (in):	9.25 in	Bore Size Max (mm):	235 mm
Bore Type:	Finish Bore	Compatible Bore Size [Min] (in):	4.65 in
Compatible Bore Size [Min] (mm):	118 mm	Configuration:	Full Flex Coupling
Coupling Size:	600	Coupling Type:	Barflex Coupling
Fastener Quantity:	10	Flange Thickness (mm):	20 mm
Hub Diameter (mm):	330 mm	Includes:	Hub (1) Sleeve (1) Cover (1) Pin (1) Pointer (1) Seeger Ring (1) Barrel Set (1) Fastner Set (1)
Length Through Bore (in):	9.45 in	Length Through Bore (mm):	240 mm
Lube/Non-Lube:	Lubricated	Material:	Alloy Steel
Maximum Displacement (+/-) (mm):	6 mm	Maximum Operating Angular Misalignment:	1 °
Outside Diameter (in):	21.65 in	Outside Diameter (mm):	550 mm
Overall Length (in):	9.69 in	Overall Length (mm):	246 mm
Radial Load (N):	143,650 N	Sleeve Type:	Flanged
Style:	TCBR	Temperature Range:	-15°C to 60°C
Torque [Max] (in-lb):	1,222,730.53 in/lbs	Torque [Max] (N-m):	138,150 N-m

How can we improve our Product Information?

Print

Resource Center

2D/3D CAD



Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS