



Jaure Barflex Barflex Coupling -Style TCBR - Heavy Duty Standard Design - Size 1000 -Full Flex -Finish Bore - BARFLEX TCBR-1000 B01

Part #: ABBR0010039 Catalog #: BARFLEX TCBR-1000 B01



☐ Add to Compare

UOM: EA

WHERE TO BUY



☐ Compare Product

KEY FEATURES

- About 10% higher torque capacity, allowing a more favorable size selection and thus an important cost saving
- Assembly time reduction
- Increased axial misalignment tolerance
- Improved visual wear indicator. Easier to read wear

PRODUCT SPECIFICATIONS

Technical Specifications

Technical Specifications			
Bolt Circle:	530	Bolt Type:	Exposed Bolt
Bore Size Max (in):	9.84 in	Bore Size Max (mm):	250 mm
Bore Type:	Finish Bore	Compatible Bore Size [Min] (in):	5.43 in
Compatible Bore Size [Min] (mm):	138 mm	Configuration:	Full Flex Coupling
Coupling Size:	1000	Coupling Type:	Barflex Coupling
Fastener Quantity:	14	Flange Thickness (mm):	20 mm
Hub Diameter (mm):	368 mm	Includes:	Hub (1) Sleeve (1) Cover (1) Pin (1) Pointer (1) Seeger Ring (1) Barrel Set (1) Fastner Set (1)
Length Through Bore (in):	10.24 in	Length Through Bore (mm):	260 mm
Lube/Non-Lube:	Lubricated	Material:	Alloy Steel
Maximum Displacement (+/-) (mm):	6 mm	Maximum Operating Angular Misalignment:	1 °
Outside Diameter (in):	22.83 in	Outside Diameter (mm):	580 mm
Overall Length (in):	10.47 in	Overall Length (mm):	266 mm
Radial Load (N):	158,050 N	Sleeve Type:	Flanged
Style:	TCBR	Temperature Range:	-15°C to 60°C
Torque [Max] (in-lb):	1,640,043.19 in/lbs	Torque [Max] (N-m):	185,300 N-m

How can we improve our Product Information?

Print

Resource Center

2D/3D CAD

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS