



Jaure Barflex Barflex Coupling -Style TCBR - Heavy Duty Standard Design - Size 2100 -Full Flex -Finish Bore - BARFLEX TCBR-2100 B01

Part #: ABBR0010122 Catalog #: BARFLEX TCBR-2100 B01



☐ Add to Compare

UOM: EA

WHERE TO BUY



☐ Compare Product

KEY FEATURES

- About 10% higher torque capacity, allowing a more favorable size selection and thus an important cost saving
- Assembly time reduction
- Increased axial misalignment tolerance
- Improved visual wear indicator. Easier to read wear

PRODUCT SPECIFICATIONS

Technical Specifications

Technical Specifications

Bolt Circle:	615
Bore Size Max (in):	12.01 in
Bore Type:	Finish Bore
Compatible Bore Size [Min] (mm):	168 mm
Coupling Size:	2100
Fastener Quantity:	26
Hub Diameter (mm):	456 mm
Length Through Bore (in):	12.99 in
Lube/Non-Lube:	Lubricated
Maximum Displacement (+/-) (mm):	10 mm
Outside Diameter (in):	26.18 in
Overall Length (in):	13.39 in
Radial Load (N):	288,850 N
Style:	TCBR
Torque [Max] (in-lb):	3,376,559.51 in/lbs

Bolt Type:	Exposed Bolt
Bore Size Max (mm):	305 mm
Compatible Bore Size [Min] (in):	6.61 in
Configuration:	Full Flex Coupling
Coupling Type:	Barflex Coupling
Flange Thickness (mm):	25 mm
Includes:	Hub (1) Sleeve (1) Cover (1) Pin (1) Pointer (1) Seeger Ring (1) Barrel Set (1) Fastner Set (1)
Length Through Bore (mm):	330 mm
Material:	Alloy Steel
Maximum Operating Angular Misalignment:	1 °
Outside Diameter (mm):	665 mm
Overall Length (mm):	340 mm
Sleeve Type:	Flanged
Temperature Range:	-15°C to 60°C
Torque [Max] (N-m):	381,500 N-m

How can we improve our Product Information?

Resource Center

2D/3D CAD

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS

Print

