



Jaure Barflex Barflex Coupling -Style TCBR - Heavy Duty Standard Design - Size 4200 -Full Flex -Finish Bore - BARFLEX TCBR-4200 B01

Part #: ABBR0010125 Catalog #: BARFLEX TCBR-4200 B01

☐ Add to Compare

UOM: EA

WHERE TO BUY

⊕ Hover to zoom

How can we improve our Product Information?

Print

Resource Center

2D/3D CAD

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS

☐ Compare Product

KEY FEATURES

- About 10% higher torque capacity, allowing a more favorable size selection and thus an important cost saving
- Assembly time reduction
- Increased axial misalignment tolerance
- Improved visual wear indicator. Easier to read wear

PRODUCT SPECIFICATIONS

Technical Specifications

Technical Specifications

Bolt Circle:	730
Bore Size Max (in):	15.16 in
Bore Type:	Finish Bore
Compatible Bore Size [Min] (mm):	228 mm
Coupling Size:	4200
Fastener Quantity:	26
Hub Diameter (mm):	563 mm
Length Through Bore (in):	16.14 in
Lube/Non-Lube:	Lubricated
Maximum Displacement (+/-) (mm):	12 mm
Outside Diameter (in):	30.71 in
Overall Length (in):	16.61 in
Radial Load (N):	426,000 N
Style:	TCBR
Torque [Max] (in-lb):	5,891,498.92 in/lbs

Bolt Type:	Exposed Bolt
Bore Size Max (mm):	385 mm
Compatible Bore Size [Min] (in):	8.98 in
Configuration:	Full Flex Coupling
Coupling Type:	Barflex Coupling
Flange Thickness (mm):	35 mm
Includes:	Hub (1) Sleeve (1) Cover (1) Pin (1) Pointer (1) Seeger Ring (1) Barrel Set (1) Fastner Set (1)
Length Through Bore (mm):	410 mm
Material:	Alloy Steel
Maximum Operating Angular Misalignment:	1 °
Outside Diameter (mm):	780 mm
Overall Length (mm):	422 mm
Sleeve Type:	Flanged
Temperature Range:	-15°C to 60°C
Torque [Max] (N·m):	665,650 N·m