Jaure Barflex Barflex Coupling -Style TCBR - Heavy Duty Standard Design - Size 8200 -Full Flex -Finish Bore - BARFLEX TCBR-8200 B01

Part #: ABBR0010046 **Catalog #:** BARFLEX TCBR-8200 B01

Add to Compare

UOM: EA

WHERE TO BUY

How can we improve our Product Information?

Print

Resource Center

Talk to one of our expert sales professionals about how this brand can efficiently power your business.

CONTACT OUR EXPERTS

Compare Product

KEY FEATURES

- About 10% higher torque capacity, allowing a more favorable size selection and thus an important cost saving
- Assembly time reduction
- Increased axial misalignment tolerance
- Improved visual wear indicator. Easier to read wear

PRODUCT SPECIFICATIONS

Technical Specifications

Technical Specifications

Bolt Circle:	**875**	Bolt Type:	**Exposed Bolt**
Bore Size Max (in):	**17.91 in**	Bore Size Max (mm):	**455 mm**
Bore Type:	**Finish Bore**	Compatible Bore Size [Min] (in):	**10.04 in**
Compatible Bore Size [Min] (mm):	**255 mm**	Configuration:	**Full Flex Coupling**
Coupling Size:	**8200**	Coupling Type:	**Barflex Coupling**
Fastener Quantity:	**32**	Flange Thickness (mm):	**40 mm**
Hub Diameter (mm):	**673 mm**	Includes:	**Hub (1) Sleeve (1) Cover (1) Pin (1) Pointer (1) Seeger Ring (1) Barrel Set (1) Fastner Set (1)**
Length Through Bore (in):	**19.69 in**	Length Through Bore (mm):	**500 mm**
Lube/Non-Lube:	**Lubricated**	Material:	**Alloy Steel**
Maximum Displacement (+/-) (mm):	**12 mm**	Maximum Operating Angular Misalignment:	**1 °**
Outside Diameter (in):	**37.01 in**	Outside Diameter (mm):	**940 mm**
Overall Length (in):	**21.3 in**	Overall Length (mm):	**541 mm**
Radial Load (N):	**525,000 N**	Sleeve Type:	**Flanged**
Style:	**TCBR**	Temperature Range:	**-15°C to 60°C**
Torque [Max] (in-lb):	**7,965,671.19 in/lbs**	Torque [Max] (N·m):	**900,000 N·m**