



KOP-FLEX™



List Price: \$6,918.03

WHERE TO BUY

☐ **Compare Product**

- Close Coupled disc coupling design with reversible hubs to accommodate various shaft separations.
- Semi-Unitized Disc Packs for ease of maintenance, replaceable without moving the connected equipment.
- HS (High Torque, Semi-unitized) disc packs for medium and heavy duty applications.
- Meet AGMA Class 8 balance off the shelf, and may be component balanced to AGMA Class 9.

General Specifications

Axial Capacity (+/-):	0.08
Bore Type:	Finished Bore
Coupling Size:	103
Length Through Bore standard hub (in):	1.69 in
Speed Max Balanced (rpm):	9,700 rpm
Torque [Max] (ft-lb):	667 ft/lbs
Total Length (One Hub Reverse) (in):	4.94 in
Total WR2 (lb-in2):	16 psi

Bore Size Min (in):	0.5 in
Configuration:	2 standard hubs
Hub Material:	Carbon Steel
Outside Diameter (in):	3.94 in
Style:	KD10
Torque Rating (in-lb):	4,000 in/lbs
Total Length (Std Hub Post) (in):	3.5 in

Print

- 2D/3D CAD
- Catalog Page
- Installation Manual

CONTACT OUR EXPERTS